



备注

- (1) 这款骨架材料要求T220NA，要求PIN拉拔力焊前大于1.0kg，焊后大于1.2kg
- (2) 材料符合汽车禁限用物质要求，无卤无红磷

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	增加一个过线槽	2024/10/16	03		
02	增加两个0.60mm过线槽;PIN5 处小缺口填平;PIN7旁0.6线槽改为1.0; 顶部增加一个小线槽0.8*0.8	2025/02/08	04		

NAME	EE-10 (8P)	MATERIAL	T220NA	SCALE	1:1	ANGLE	±1°	
DRAWING NO.	HX-1053	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	02	
<p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com</p>		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD kg MIN		UL REC. :94V0
		TOLERANCE:0<L<4:±0.1 4<L<16:±0.2 16<L<63:±0.3		DRAWN & DRAFTED BY		LIN HUA JING	CHECKED & APPROVED BY	