



備註說明:

1. 材質: PM-9823
2. U型PIN: 材質C1100, $\phi 1.40 \pm 0.05$
3. 耐壓要求: 任意位置 4. 0KV/1.5mA/60S
4. 焊錫溫度: $440^{\circ} \pm 10^{\circ}$ 3SEC
5. 拉力: 焊前 1.0kg MIN, 焊後 1.5g MIN
6. 模具狀況: 樣品模

客户确认
签回

RoHS
HF

| REV. | REVISION RECORD | DATE | REV | REVISION RECORD | DATE |
|------|-----------------|------|-----|-----------------|------|
| 01 | | | 03 | | |
| 02 | | | 04 | | |

| | | | | | | | |
|-------------|--------------|--------------|---------|-------|-----|-------|-----------------|
| NAME | EE-10.4 (5P) | MATERIAL | PM-9823 | SCALE | 1:1 | ANGLE | $\pm 1^{\circ}$ |
| DRAWING NO. | HX-1058 | PIN MATERIAL | CP WIRE | UNIT | m/m | REV. | 00 |



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

| | | |
|----------------------|--|-----------------------|
| TOLERANCE OF PIN DIA | ± 0.05 | |
| PIN TENSION LOAD | kg MIN | UL REC. : 94V0 |
| TOLERANCE: | $0 < L < 4 : \pm 0.1$ $4 < L < 16 : \pm 0.2$ $16 < L < 63 : \pm 0.3$ | |
| DRAWN & DRAFTED BY | LIN HUA JING | CHECKED & APPROVED BY |
| DATE: | JUN 13 2025 | |