



PIN咬花外露(客戶力信要求)  
DETAIL B(2:1)



備註:

1. 材質: PM-9630
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/60S
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 正式模

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	增加PIN腳外露咬花	2022/06/15	03		
02			04		

NAME	EE-13(10P)	MATERIAL	PM-9630	SCALE	3:1	ANGLE	±1°
DRAWING NO.	HX-1343	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01



东莞市华欣塑胶制品有限公司  
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD.  
TEL:0769-86388088 86388188 86388288 FAX:0769-86388111  
http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	±0.05	
PIN TENSION LOAD	1.0 kg MIN	UL REC. :94V0
TOLERANCE: 0<L≤4: ±0.1	4<L≤16: ±0.2	16<L≤63: ±0.3
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	JUL 04 2008	