



備註說明:

1. 耐壓要求: 3KV/0.5mA/3SEC
2. 焊錫溫度: 450° ±10° 3SEC
3. 拉力: 焊前 0.75kg MIN; 焊后 1.0kg MIN
4. 模具狀況: 正式模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EP-13(10P)	MATERIAL	PM-9823	SCALE	1/1	ANGLE	±1°
DRAWING NO.	HX 1336	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
<p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com</p>		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD 1.0 kg MIN	
		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3				UL REC. :94V0	
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: FEB 14 2020	