



備註說明:

1. 材質: PM-9630
2. 強度要求: 2.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ± 10° 3SEC
5. 模具狀況: 量產模
6. HX-0820B與HX-0815A/HX-0820A裝配

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	A尺寸由23.7改为23.9+0.1/-0.2, F尺寸由25.3改为25.5+0.1/-0.2	2015/04/11	03	凸點線槽寬度由1.20改為0.60(mm)	2015/04/11
02	底部槽口內徑由6.1改為7.1, 槽口外徑由7.1改為8.1	2015/04/11	04		

NAME	RM-8 CAP	MATERIAL	PM-9630	SCALE	1/1	ANGLE	±1°
DRAWING NO.	HX-0820B	PIN MATERIAL		UNIT	m/m	REV.	B
 <p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>	TOLERANCE OF PIN DIA ±0.05		— ⊕ —		UL REC. :94V0		
	PIN TENSION LOAD kg MIN		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3				
	DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	MAY 19 2014	