



備註說明:

- PART NO. : HX-0822B 正式模
- MATERIAL: PM-9630 MUST MEET UL94V-0
- COLOR: BLACK
- CORE TYPE: RM-8
- MATERIAL OF PIN : 3/4H CP WIRE, SQ0.60±0.05
- DIMENSION MARK :  $\triangle$  MAIN DIM.,  $\otimes$  SECOND DIM, OTHERWIRE ARE REFERENTIAL DIM. .  
标示的  $\triangle$  为重要尺寸, 标示的  $\otimes$  为次要尺寸。

BOBBIN與CASE組合腳位尺寸圖

- 強度要求: 1.50kg MIN
- 耐壓要求: 4KV/1.5mA/1分鐘
- 焊錫溫度: 450° ±10° 3SEC
- 拉力: 焊後拉力 1.5kg MIN
- HX-0822A與HX-0822B匹配OK

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	RM-8 (2P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-0822B	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 1.0 kg MIN TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		 UL REC. :94V0	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	APR 02 2014		