



備註說明:

1. 材質: PM-9820
2. 強度要求: 1.30kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 模具狀況: 正式模
6. 底部不可有變形拱起現象.
7. HX-1034A與HX-1034B裝配

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	RM-10 CAP	MATERIAL	PM-9820	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-1034B	PIN MATERIAL		UNIT	m/m	REV.	00
 <p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com</p>	TOLERANCE OF PIN DIA ±0.05		— ⊕ —		UL REC. :94V0		
	PIN TENSION LOAD kg MIN		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3				
	DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	JUN 13 2013	