



備註說明:

1. 材質: PM-9630
2. 強度要求: 2.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: (1)PIN 1, 2, 5, 6焊錫前後拉力 1.00kg MIN  
(2)PIN 3, 4焊錫前後拉力 1.50kg MIN
6. 模具狀況: 正式模

客户确认  
簽回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	UU-0306 (6P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-0301	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司  
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.  
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111  
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	±0.05	
PIN TENSION LOAD	1.0 kg MIN	UL REC. :94V0
TOLERANCE:	0<L≤4: ±0.1    4<L≤16: ±0.2    16<L≤63: ±0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	MAY 21 2014	