


備註說明:

1. 材質: PM-9630
2. 強度要求: 1.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊前是1.00kg MIN, 焊後是1.50kg MIN
6. 模具狀況: 樣品模



A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	客户确认 签回	RoHS HF
6.48	8.40	4.30	7.13	3.30	2.20	4.30	5.40	14.80	3.40	0.50	2.85	2.85	2.85	0.55	0.55	PL	10.75	2.40	6.50			
±0.2	±0.2	+0.15/-0.05	±0.2	±0.1	+0.15/-0.05	+0.15/-0.05	±0.2	±0.2	±0.1	±0.05	±0.1	±0.1	±0.1	±0.05	±0.05	±0.2	±0.2	±0.1	±0.2			
REV.	REVISION RECORD												DATE	REV	REVISION RECORD					DATE		
01														03								
02														04								

NAME	UU-8.65(2P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-0829	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com	TOLERANCE OF PIN DIA ±0.05						
	PIN TENSION LOAD kg MIN			UL REC. :94V0			
	TOLERANCE:0<L<4:±0.1 4<L<16:±0.2 16<L<63:±0.3						
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	MAY 29 2018		